

Antifreeze Reference Chart

Technical Support / Re-Order: 1-800-315-4467
www.SolventsandPetroleum.com



	Conventional	Extended Life OAT	Heavy Duty Extended Life OAT	Universal Extended Life HOAT	Heavy Duty Nitrite-Free OAT
Formulation	Conventional Service Formula	Extended Life Formula	Extended Life Formula	Extended Service Formula	Extended Life Formula
Color	Green	Orange	Strawberry	Yellow	Red
Base	EG or PG	EG or PG	EG or PG	EG or PG	EG or PG
Best Use	Older Gasoline Automobiles & Heavy Duty Diesel Trucks / Equipment	Newer Automobiles & Light Duty Gasoline Engines	Newer Heavy Duty Diesel Engines	Virtually Any Vehicle & Heavy Duty Diesel Engines	Heavy Duty Diesel Engines
Recommended Change Interval	Every 30,000 Miles or as Appropriate When Tested w/ Test Strips. Longevity of 2 Years / 200,000 Miles w/ Use of TYPE 2 SCA	5 Years / 150,000 Miles	3 Years / 300,000 Miles then Boosted to 6 Years / 600,000 Miles w/ Extender	30,000 Miles then Boosted to 3 Years / 300,000 Miles w/ Type 4 SCA Extender	3 Years / 300,000 Miles then Boosted to 6 Years / 600,000 Miles w/ Extender at Half-Life
Nitrites	✓	None	✓	✓	None
Phosphates	None	None	None	None	None
Silicates	Low	None	None	Low to None	None
Corrosion Protection	✓	✓	✓	✓	✓
Freeze Point	-34°F	-34°F	-34°F	-34°F	-34°F
Boil-Over Temperature	265°F	265°F	265°F	265°F	265°F
pH Level	7.5 - 11	7.5 - 11	7.5 - 11	7.5 - 11	7.5 - 11
Product Warranty	✓	✓	✓	✓	✓

Concentrated and Ready-to-Use Blends Available