



Heavy Duty Global Extended Life

Organic Acid Technology (OAT)

PROFLEET® Heavy Duty Global Extended Life Antifreeze / Coolant is an advanced Organic Acid Technology (OAT) antifreeze for heavy-duty diesel engines that protects against damaging rust and corrosion. This type antifreeze does not contain nitrites, amines, phosphates, silicates or 2-Ethylhexanoic acid (2-EH). It is formulated with scale inhibitors and dispersants and is safe for elastomers used in hoses and gaskets. Supplemental Coolant Additive (SCA) are not required. PROFLEET® Heavy Duty Global Extended Life is compatible for top-off and service with other modern OAT and NOAT formulations.



Best Use: Newer Heavy Duty Diesel Engines

Recommended Service Interval: 3 Years / 300,000 Miles then Boosted to 6 Years / 600,000 with Extender

BENEFITS

- ◆ Propylene Glycol or Ethylene Glycol Base
- ◆ Concentrated or Ready-to-Use (50/50 Pre-mix w/ DI Water)
- ◆ Bulk, mini-bulk, totes, drums, or one gallon containers
- ◆ Extended Life Coolant (ELC)
- ◆ Compatible with modern OAT antifreeze / coolants
- ◆ Product Performance Warranty

SPECIFICATIONS

- ◆ ASTM D6210 for Heavy-Duty Engines
- ◆ ASTM D3306 for Automobile & Light-Duty Service
- ◆ ASTM D7583 for John Deere Cavitation Test
- ◆ Free from amines, phosphates, silicates, and 2-ethylhexanoic acid (2-EH)

MEETS REQUIREMENTS

- ◆ Caterpillar, Cummins, Detroit Diesel, Freightliner, International, Mack, and Volvo, and more
- ◆ Phosphate-free requirement of European OEMs
- ◆ Silicate-free requirement of Japanese OEMs
- ◆ TMC RP-329 (EG)

PROFLEET® is compatible with several competing brands of antifreeze. Refer to the Compatibility Chart for more information.



PROFLEET® Manufactured by:
Solvents & Petroleum Service, Inc.
1405 Brewerton Road | Syracuse, NY 13208

For Technical or Ordering Information Call 1-800-315-4467

www.PROFLEETAntifreeze.com

Table of Properties & Typical ASTM Test Results

Test / Property	ASTM Test Method	EG Concentrate	EG 50/50
Color	Visual	Yellow	Yellow
Relative Density, 15.5/15.5°C (60/60°F)	D1122	1.1188	1.065 min
Freezing Point °C (°F), 50 vol % in DI water	D1177	N/A	-37.3 (-35.1)
Boiling Point °C (°F), 50 vol % in DI water	D1120	N/A	108 (226)
pH, 50% vol % in DI water	D1287	N/A	8.69
Reserve Alkalinity ¹ , mL	D1121	5.0	report
Ash Content, mass %	D1119	5 max	0.4
Chloride, µg/g	D3634	4 mg/kg	25 max
Water, mass %	D1123	4.5	N/A
Foaming Tendencies, mL/sec	D1881	N/A	105/2.5
Glassware Corrosion test	D1384	Pass	Pass
Aluminum Water Pump Cavitation Test	D2809	Pass	Pass
Aluminum Corrosion Test	D4340	Pass	Pass
Auto Finish Effect	D1882	No Effect	No Effect
Simulated Service Corrosion Test	D2570	Pass	Pass

Note 1: Modern OAT coolants do not require high reserve alkalinity to perform exceedingly well.

The preceding data is based on tests and experience, which Solvents and Petroleum Service, Inc. believes reliable, and is supplied for informational purposes only. For detailed safety and handling information regarding these products, please refer to the respective Solvents and Petroleum Service, Inc. Safety Data Sheets (SDS).

	Packaging	EG 50/50 Premix	EG Concentrated
Part Numbers	Bulk	PROHDG01-PB	PROHDG01-CB
	Tote (275 Gallons)	PROHDG01-PT	PROHDG01-CT
	Drum (55 Gallons)	PROHDG01-PD	PROHDG01-CD
	Pail (5 Gallons)	PROHDG01-PL	PROHDG01-CL
	Case (6, 1-Gallon Jugs)	PROHDG01-PC	PROHDG01-CC
	Jug (1 Gallon)	PROHDG01-PJ	PROHDG01-CJ



PROFLEET® Manufactured by:
 Solvents & Petroleum Service, Inc.
 1405 Brewerton Road | Syracuse, NY 13208

For Technical or Ordering Information Call 1-800-315-4467

www.PROFLEETAntifreeze.com